BP-70M31

Future proofed by design with stringent security features and superior functionality for hybrid working



- 31ppm black & white MFP with seamless integration and connection to cloud based business process applications
- Built-in Microsoft® Teams connector strengthens collaboration by enabling direct and secure access for printing to or scanning from your Microsoft® Teams channels
- Keep your data, device and network secure with optional Bitdefender anti-malware protection software
- Securely print from or scan to public cloud storage services quickly and easily with single sign-on
- Scan at speeds of up to 280ipm with optional double feed detection for eliminating productivity interruptions
- Superior environmental performance delivers lower standby power consumption and low TEC value

- Feature rich hardware and solutions platform that supports the hybrid working environment
- Industry leading system and data protection features including BIOS based security and standard Trusted Platform Module ensure that confidential data is kept secure
- Interact with the MFP directly from your mobile device via WiFi, AirPrint, Bluetooth, NFC and QR Code
- 10.1-inch colour LCD operation panel offers a smartphone style user interface making everything easy to access and use
- Extensive finishing options including a folding unit bring even more flexibility to your print output
- Keep up-to-date and compliant with remote firmware and application updates via the Sharp Application Portal





Specifications

Engine speed B/W ppm (A4) 31 Engine speed B/W ppm (A3) 15 Paper size: Min.-Max. AGR - A3W Paper weight (g/m2) 55 - 300 Paper capacity:Std (sheets) 650 Paper capacity: Max. (sheets) 6300 Warm Up Time (sec.) 14 Memory general min/max (GB) SSD STD / OPT SSD Capacity (GB) 256 / 512 STD Duplex 220 - 240V, 50 / 60Hz

Power requirements - rated local AC voltage

Power consumption (kW) 1 84 Dimensions (mm) 609 x 662 x 860

Weight (kg)

DOCUMENT FEEDER

300 Original capacity (sheets)

DOCUMENT FILING

Document filing (Standard / Option) STD Document filing capacity- main and custom 20000 folders (pages)

Document filing capacity- quick file folder (pages)

Stored jobs Copy, print, scan, fax transmission Storage folders Quick file folder, main folder, custom folder (max. 1000)

Fax (Standard / Option) MH / MR / MMR / JBIG Compression method Communication protocol Super G3 / G3 Transmission time (sec)

Modem Speed (bps) 33600 - 2400 STD 203.2 x 97.8 dpi / Ultra Fine Transmission resolution

406.4 x 391 dpi

Document Size (Min) Α5 Document Size (Max) АЗ Memory (GB) **Grev Scale levels** 256 Dial Registration; rapid/speed dial 2000

Broadcast Transmission (max. destinations)

WIRFLESSIAN

Wireless LAN (Standard / Option) Compliant regulation

IEEE802.11 a / b / g / n / ac Access mode Infrastructure mode, Software AP mode

500

Security WEP, WPA / WPA2-mixed PSK, WPA

/ WPA2-mixed EAP, WPA2-PSK, WPA2-FAP WPA2 / WPA3-mixed PSK / SAE, WPA3 SAE, WPA2 / WPA3-mixed EAP, WPA3 EAP

COPIER

Original paper size (Max.) Δ3 First copy out time B/W (sec.) 5.4 E-sort Std Continuous copy (Max. copies) 9,999 Resolution Scan B/W (dpi) 600 x 600, 600 x 400, 600 x 300

Resolution Scan Colour (dpi) 600 x 600 Resolution Print (dpi) 1200 x 1200, 600 x 600, 9600 x 600 Gradation (equivalent levels) - B/W

Gradation (equivalent levels) - Colour 256 Zoom range (%) Preset copy ratios

Network Scanner (Standard / Option) Scan method Push scan and Pull scan Resolution push scan (dpi)

Resolution pull scan (dpi)

File formats

100, 150, 200, 300, 400, 600 75, 100, 150, 200, 300, 400, 600, 50 -9600 TIFF, PDF, PDF / A-1a, PDF / A-1b,

STD

encrypted PDF, compact PDF, IPEG XPS searchable PDF Microsoft Office (pptx, xlsx, docx), TXT (UTF-8), RTF

Scan destinations Desktop Scan destination FTP, Email Scan destination Network folder Scan destination USB memory

PRINTER

Resolution (dpi) 1200 x 1200, 600 x 600, 9600 x 600 Network Printer (Standard / Option) STD Ethernet

Interface Std/Opt USB 2.0, USB 3.0, 10Base-T / 100Base-TX / 1000Base-T, Optional secondary LAN support

Windows 8.1, 10, 11. Windows **Supported OS Standard** Server 2012, 2012R2, 2016, 2019. Mac OS X 10.10, 10.11, 10.12, 10.13,

10.14, 10.15, 11, 12 TCP / IP (IPv4, IPv6) Network protocols

Printing protocols LPR, Raw TCP (port 9100), POP3 (email printing), HTTP, FTP for downloading print files, IPP, SMB,

STD PCL 6. Adobe® PostScript® 3™ PDL Std/Opt Available fonts 80 (PCL), 139 (Adobe PostScript 3)

FINISHING

Output Capacity Max. 500 - 3000 Staple Capacity (sheets) Max. OPT Saddle Stitch Off-set shifting STD Hole punch OPT

TONER YIELD

Black (pages at 6% coverage) 40000

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either uosgy in uns year-unautrs are subject to change winnout prior notice, an immanation was correct at time of print. Microsoft, Except, PowerFornt, CheDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Morbos Systems incorporated in the US and/or other countries. Google Drive, Cmail and Android are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of BOXO SWEW (Indows Services) and the US and other countries. PLC is a registered trademark in Alba are a trademarks of Apple Inc., registered in the US and other countries. PLC is a registered trademark of BOX MINE (Indows Apple Inc., registered in the US and other countries. PLC is a registered trademark of Apple Inc., registered in the US and other countries. PLC is a registered trademark of Services of Apple Inc., registered in the US and other countries. PLC is a registered trademark of Services of Apple Inc., registered in the US and other countries. PLC is a trademark of Services of Services of Apple Inc., registered trademarks of the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. @Sharp Corporation July 2022. Ref. BP-70M31 Datasheet. All trademarks acknowledged. E&O.



